

1- Introduction

Thank you for choosing Lewmar. Lewmar products are world renowned for their quality, technical innovation and proven performance. With a Lewmar product you will be provided with many years of outstanding service.

Product support

Lewmar products are supported by a worldwide network of distributors and Authorised Service Representatives. If you encounter any difficulties with this product, please contact your national distributor, or your local Lewmar dealer. Details are available at: www.lewmar.com

CE Approvals



For CE approval certificates contact Lewmar.

Important information about this manual

Throughout this manual, you will see safety and product damage warnings. You must follow these warnings carefully to avoid possible injury or damage.

2- Specification

			D (mm)	D (inch)	P (mm)	P (inch)	W (mm)	W (inch)	
Dual Gypsy	12 mm (1/2") 3 Strand and 8 Plait	6mm DIN 766	6	0.236	18.5	0.728	20.4	0.803	
		7 mm DIN 766	7	0.276	22	0.866	23.8	0.937	
		1/4" ISO G4	7	0.276	21.3	0.840	24.4	0.962	
		1/4" BBB	7.14	0.281	22.1	0.870	25.2	0.992	
RC0860 Gypsy No. 504	14-16 mm (9/16" - 5/8") 3 Strand and 8 Plait (5/8" only)	8 mm DIN 766	8	0.315	24	0.945	27.2	1.070	
		8 mm ISO 4565	8	0.315	24	0.945	28.8	1.134	
		5/16" BBB	8.73	0.343	25.4	1.000	30.1	1.186	
RC0864 Gypsy No. 516	14-16 mm (9/16" - 5/8") 3 Strand and 8 Plait (5/8" only)	8 mm DIN 766	8	0.315	24	0.945	27.2	1.070	
		8 mm ISO 4565	8	0.315	24	0.945	28.8	1.134	
		5/16" ISO G4	8.36	0.329	26.16	1.030	28.4	1.118	
Pb Gypsy	14-16 mm Lead-core line								



A		B		C	
mm	in	mm	in	mm	in
146	5 3/4	245	9 5/8	178	7

Electric specifications

MODEL	MAX CHAIN		MOTOR SUPPLY	MOTOR POWER	MAXIMUM PULL		MAXIMUM LINE SPEED		WORKING LOAD LIMIT		NORMAL CURRENT DRAW	CIRCUIT BREAKER	WEIGHT	
	mm	in	Voltage	Watt	kg	lb	m/min.	ft/min.	kg	lb	Amp	Amp	kg	lb
Pro-series/Fish 700	7	1/4	12	500	320	700	32	105	79	175	35	50	8.5	19
Pro-series/Fish 1000	8	5/16	12	700	454	1000	32	105	114	250	50	70	9.5	21
Pro-Fish Pb														